

### FEATURES

- high wattage
- compact
- quiet operation
- excellent cooking results
- efficient, reliable
- reheating and defrosting
- reduces food waste
- easy to clean

### POWER

- 1200 watts
- 5 levels – 100%, 70%, 50%, 20%, 0%
- 2 magnetrons
- top and bottom microwave feeds

### CAPACITY

- 34 litres (1.2 cu ft)
- platter size: 356mm (14")

### CONTROLS

- touch pads with Braille
- 10 pre-programmed cycles, including defrost
- can be programmed with up to 100 cycles
- auto start pre-program
- 3 stages
- X2 pad
- digital display
- end-cycle adjustable
- time entry option

### CONSTRUCTION

- stainless steel, inside and out
- internal chamber light
- grab and go handle
- stackable, with safety bracket
- removable air filter
- removable splatter guard

### OPERATION

maximum cooking time: 60 minutes

### WARRANTY

3 years parts & labour



### ELECTRICAL

120V 60Hz  
20 amp single phase  
nema plug 5-20  
1.5m (5 ft) cord



### DIMENSIONS

exterior	368mm H x 574mm W x 528mm D (14.5"H x 22.6"W x 20.8"D)
interior	226mm H x 356mm W x 406mm D (8.9"H x 14"W x 16"D)
weight	32.2 kg (71 lbs)
shipping weight	37.2 kg (82 lbs)

### SPECIFICATIONS

Commercial microwave oven will be equipped with 10 touch pads with Braille programmable control panel with the ability to program 100 menu items. Oven will have a maximum cooking time of 60 minutes with 5 power levels, 3 stage cooking and a time entry option. Output wattage shall be 1200 watts with top and bottom rotating antenna feed distribution for a uniform heating pattern. Oven will have stainless steel exterior and interior cavity with the 34 litre (1.2 cu ft) cavity able to accommodate a 356mm (14") plate. Ovens will be stackable and include a safety bracket. Removable front filter to protect and cool oven components. This ISM apparatus meets all requirements of the Canadian Interference Causing Equipment Regulations. This ISM device complies with Canadian ICES-001.



Intertek