

Master Half-Size Electric Convection Oven

Project	
Item	
Quantity	
CSI Section 11400	
Approved	
Date	

Models

- MCO-E-5-C
- MCO-E-25-C



Model MCO-E-5-C

NOTE: Ovens suppled with casters must be installed with an approved restraining device.

Standard Features

- Master 200 Solid State Control with 150° (66°C) to 500°F (260°C) temperature range, and 60 minute electromechanical timer
- 2-Speed 1/3 HP motor with thermal hi-limit and centrifugal switch protection
- 208 or 240 volt, single or three phase (please specify)
- Total of 5.6 kW elements per oven cavity
- Stainless steel front, sides, and top
- Single door with double pane thermal window
- 4" (102mm) stainless steel legs with adjustable bullet leveling leg insert.
- Porcelain enameled oven interior
- 5 chrome plated oven racks on 9-position rack guides
- Double deck models available -Suffix 25-C

Warranty

- 1 year limited parts & labor warranty (USA & Canada only)
- 5 year limited door warranty, excluding window (USA & Canada only)
- 2 year limited parts & 1 year labor warranty (USA only)
- 2 year limited parts & labor warranty (USA Kindergarden to Grade 12 schools

Optional Features

- 7.5 kW elements
- Extra oven racks
- · Stainless steel main back
- Solid stainless steel door, (no charge)
- Stainless steel equipment stand 34" (864mm) high with rack guides. (only for single deck models only)
- 21 1/4" (540mm) stainless steel legs (double deck models only)
- Cord and plug set
- Swivel casters w/front brakes (single decks overall height 31 3/4" (806mm) double stacked units overall height 57" (1448mm)

(Note: Casters can not be installed onto stands or stacked models with 21 1/4" legs.)

Specifications

- Garland Master Half-Size electric convection oven.
- 5.6 kW/cavity, 1/3 HP fan motor with two-speed control.
- Porcelain enameled oven, 5 oven racks and 9-position rack guides,
- Measures 15-1/2" (470mm)W x 20" (508mm)H x 21-1/8" (536mm)D.
- Stainless steel front, top, and sides.
- UL, CUL and NSF Listed.























Optional equipment stand for single deck models. Stand is 34" (864mm) high.

Model #	Interior Dimensions (pe	r deck)	Ship Wt.	Ship	
Model #	W	Н	D	Lbs/Kg	Cu Ft
MCO-E-5-C	15-1/2" (393mm)	20" (510mm)	21 1/8" (537mm)	340/155	38.5
MCO-E-25-C	15-1/2" (393mm)	20" (510mm)	21 1/8" (537mm)	680/310	77

		Nominal Amperes Per Line							
Package	Total kW	208V/1Ph	240V/1Ph	208V/3Ph			240V/3Ph		
				Х	Υ	Z	Х	Υ	Z
Standard	5.6	27	23	23	12	14	20	12	14
Option	7.5	39	33	23	21	22	20	18	19

Installation Notes:							
Combusti	Combustible Wall Clearances						
Sides	*1" (25.4mm)	Back	1" (25.4mm)				
*Note: Installations beside units with high heat sources it is recommended t0o leave 6" (152mm) on the right side of oven. Refer to the installation manual for more detail							
Entry Clearance							
Crated		Uncrated					
37" (940n	nm)	31" (787mm)					

NOTE: Double decks require 2 power supplies please specify electrical characteristics when ordering.

Welbilt reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd. 1177 Kamato Road, Mississauga, Ontario L4W 1X4 CANADA General Inquires 1-905-624-0260 USA Sales, Parts and Service 1-800-424-2411 Canadian Sales 1-888-442-7526 Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com 6869A 12/20

