

NAPOLI-125 ROTATING OVEN

Code:

Fuel Options: • N-125G-Gas

• N-125

Baking Surface:

• Rotating

Overview

This latest addition to our wood-fired pizza ovens has already seduced pizza makers across Europe and North America. Its bold shape and vibrant style makes the Napoli the perfect focal point in your restaurant and a great conversation piece for your patrons.

Rotating ovens are ideal for fast-paced, high volume baking while still emphasizing production quality. It allows you to minimize the number of staff required, and maximize the use of your workspace.

Pizza Capacity

8"	10"	12"	14"	16″	18″	20"
22	16	11	7	5	4	3

Standard Features

- Constructed with vibrated refractory stone
- Suitable for various foods: pizza, pita, bread, slow cooking meat & fish
- Heats up rapidly up to 950° Fahrenheit (510°C)
- Efficient temperature maintenance with no heat loss
- Heavy duty steel stand
- Rotating refractory stone baking surface
- Touch screen rotation and gas controller

Certification

• ETL approved for Canada/USA

Warranty Information

- 4 Year deck and dome refractory stone warranty
- 1 Year parts and labour warranty

<image>

Images for demonstrative purposes only. Equipment shown may not be included in your custom quote. Images are not to scale. Consult quote for custom options.

Standard Finish

- Plain unfinished
- Additional colours or finishes are extra (see quote)


Customization Options


- Delivered assembled or assembled on site.
- Custom mosaic colour, pattern and branding
- Several door options, sizes and colours available
- Granite mantle
- Left or right burner position
- Propane or Natural Gas
- Debris collector
- Oven tools






NAPOLI-125 ROTATING OVEN N-125








Clearance requirement is 3" (8cm) on all sides and 6" (16cm) on the top. Optional granite mantle pictured

Fuel Position

Left side standard, right side optional.



Gas Requirements)

- 99,000 BTUs, 3/4" NPT
- Inlet pressure for natural gas 7" water column

• Inlet pressure for liquid propane gas 11" water column Gas components must be accessible at all times for maintenance purposes.

Venting Requirements

Vent Type	Gas
Direct Vent	✓
Hood Vent	✓

- The oven is vented through a 7¾" round duct collar.
- Direct Venting requires a double wall chimney pipe.
- Direct vent flue adapter available: 7³/₄"-8"
- Hood Venting requires installation under a type 1 exhaust hood. Installation & venting is subject to the local authorities approval.

Oven base height is 81"(205cm). The legs may be extended by 5¾"(15cm) to increase height to 861/2" (220cm) & the deck to 471/4" (120cm).

Flectrical Information

All rotating ovens supplied with a state-of-the-art touch screen controller to control rotation, and gas if equipped.

Controller Power		Plug	Cord	
Touch Screen	220V/1phase	NEMA 6-15P 🕀	9'	274cm

Size Specifications

Oven Specifications		
Uven Specifications		Constitutions
	Oven	specifications

Baking Area	Width	Depth	Height	Weight
ø 49½"	69"	74"	81"	4200Lbs
ø 125cm	174cm	187cm	205cm	1900Kg

Shipping Specifications (Assembled in crate)

Width	Depth	Height	Weight
85"	93"	86"	4696Lbs
217cm	237cm	218cm	2130Kg

Shipping Specifications (Unassembled in crates)

	Width	Depth	Height	Weight
Crate 1	82"	43"	85"	5071Lb
	208cm	108cm	216cm	(Total)
Crate 2	70"	58"	54"	2300Kg
	178cm	148cm	136cm	(Total)

Shipping weight and dimensions are approximate and will change based on tiling selection, sill inclusion and fuel type.



GAS