

NAPOLI-115 ROTATING OVEN

Code:

• N-115

- Fuel Options:
- N-115W-Wood

Baking Surface:

• Rotating

N-115G-Gas
N-115C-Combi

Overview

This latest addition to our wood-fired pizza ovens has already seduced pizza makers across Europe and North America. Its bold shape and vibrant style makes the Napoli the perfect focal point in your restaurant and a great conversation piece for your patrons.

Rotating ovens are ideal for fast-paced, high volume baking while still emphasizing production quality. It allows you to minimize the number of staff required, and maximize the use of your workspace.

Pizza Capacity

8"	10"	12"	14"	16″	18″	20"
20	13	9	7	4	4	2

Standard Features

- Constructed with vibrated refractory stone
- Suitable for various foods: pizza, pita, bread, slow cooking meat & fish
- Heats up rapidly up to 950° Fahrenheit (510°C)
- Efficient temperature maintenance with no heat loss
- Heavy duty steel stand
- Rotating refractory stone baking surface
- Touch screen rotation controller, also controls gas on gas equipped ovens.

Certification

• ETL approved for Canada/USA

Warranty Information

- 4 Year deck and dome refractory stone warranty
- 1 Year parts and labour warranty



Images for demonstrative purposes only. Equipment shown may not be included in your custom quote. Images are not to scale. Consult quote for custom options.

Standard Finish

- Plain unfinished
- Additional colours or finishes are extra (see quote)


Customization Options


- Delivered assembled or assembled on site.
- Custom mosaic colour, pattern and branding
- Several door options, sizes and colours available (See brochure)
- Granite mantle
- Left or right burner position (gas/combi ovens)
- Propane or Natural Gas (gas/combi ovens)
- Debris collector
- Oven tools



NAPOLI-115 ROTATING OVEN N-115







Clearance requirement is 3" (8cm) on all sides and 6" (16cm) on the top. Optional granite mantle pictured

Fuel Position

WOOD GAS COMBINED

Gas Requirements (if equipped)

- 99,000 BTUs, 3/4" NPT
- Inlet pressure for natural gas 7" water column
- Inlet pressure for liquid propane gas 11" water column


Gas components must be accessible at all times for maintenance purposes.

Venting Requirements

Vent Type	Wood	Gas	Combi
Direct Vent	✓	✓	√
Hood Vent		✓	

• The oven is vented through a 73/4" round duct collar.

- Direct Venting requires a double wall chimney pipe.
- Direct vent flue adapter available: 73/4"-8"
- Hood Venting requires installation under a type 1 exhaust hood. Installation & venting is subject to the local authorities approval.



Oven base height is 81"(205cm). The legs may be extended by 5%"(15cm) to increase height to 86%"(220cm) & the deck to 47%"(120cm).

Electrical Information

All rotating ovens supplied with a state-of-the-art touch screen controller to control rotation, and gas if equipped.

Controller	Power	Plug	Cord	
Touch Screen	220V/1phase	NEMA 6-15P 🕀	9'	274cm

Size Specifications

Baking Area	Width	Depth	Height	Weight
ø 45¼"	69"	74"	81"	3750Lbs
ø 115cm	174cm	187cm	205cm	1700Kg

Shipping Specifications (Assembled in crate)

Width	Depth	Height	Weight
76"	82"	86"	4189Lbs
192cm	207cm	218cm	1900Kg

Shipping Specifications (Unassembled in crates)

	Width	Depth	Height	Weight
Crate 1	82"	43"	85"	4630Lb
	208cm	108cm	216cm	(Total)
Crate 2	70"	58"	54"	2100Kg
	178cm	148cm	136cm	(Total)

Shipping weight and dimensions are approximate and will change based on tiling selection, sill inclusion and fuel type.



Left side standard, right side optional.