

# NAPOLI-95 ROTATING OVEN

#### Code:

#### • N-95

# Baking Surface:

Rotating

# Fuel Options:

- N-95W-Wood
- N-95G-Gas
- N-95C-Combi

#### Overview

This latest addition to our wood-fired pizza ovens has already seduced pizza makers across Europe and North America. Its bold shape and vibrant style makes the Napoli the perfect focal point in your restaurant and a great conversation piece for your patrons.

Rotating ovens are ideal for fast-paced, high volume baking while still emphasizing production quality. It allows you to minimize the number of staff required, and maximize the use of your workspace.

# Pizza Capacity

8"	10"	12"	14"	16"	18"	20"
14	8	6	4	3	2	1

# Standard Features

- Constructed with vibrated refractory stone
- Suitable for various foods: pizza, pita, bread, slow cooking meat & fish
- Heats up rapidly up to 950° Fahrenheit (510°C)
- Efficient temperature maintenance with no heat loss
- · Heavy duty steel stand
- Rotating refractory stone baking surface
- Touch screen rotation controller, also controls gas on gas equipped ovens.

#### Certification

• ETL approved for Canada/USA

# Warranty Information

- 4 Year deck and dome refractory stone warranty
- 1 Year parts and labour warranty



Images for demonstrative purposes only. Equipment shown may not be included in your custom quote. Images are not to scale. Consult quote for custom options.

# Standard Finish

- Plain unfinished
- Additional colours or finishes are extra (see quote)

# Customization Options


- Delivered assembled or assembled on site.
- Custom mosaic colour, pattern and branding
- Several door options, sizes and colours available (See brochure)
- Granite mantle
- Left or right burner position (gas/combi ovens)
- Propane or Natural Gas (gas/combi ovens)
- Debris collector
- · Oven tools









# NAPOLI-95 ROTATING OVEN N-95










Clearance requirement is 3" (8cm) on all sides and 6" (16cm) on the top. Optional granite mantle pictured

#### **Fuel Position**

Left side standard, right side optional.







WOOD

COMBINED

# Gas Requirements (if equipped)

- 99,000 BTUs, 3/4" NPT
- Inlet pressure for natural gas 7" water column
- Inlet pressure for liquid propane gas 11" water column

Gas components must be accessible at all times for maintenance purposes.

# Venting Requirements

Vent Type	Wood	Gas	Combi
Direct Vent	✓	✓	✓
Hood Vent		<b>√</b>	

- The oven is vented through a 73/4" round duct collar.
- Direct Venting requires a double wall chimney pipe.
- Direct vent flue adapter available: 73/4"-8"
- Hood Venting requires installation under a type 1 exhaust hood. Installation & venting is subject to the local authorities approval.

Oven base height is 81"(205cm). The legs may be extended by 5%"(15cm) to increase height to 86%"(220cm) & the deck to 47%"(120cm).

### **Electrical Information**

All rotating ovens supplied with a state-of-the-art touch screen controller to control rotation, and gas if equipped.

Controller	Controller Power		Cord	
Touch Screen	220V/1phase	NEMA 6-15P ⊕	9'	274cm

# Size Specifications

#### Oven Specifications

Baking Area	Width	Depth	Height	Weight
ø 37½"	63"	71"	81"	3638Lbs
ø 95cm	160cm	180cm	205cm	1650Kg

#### Shipping Specifications (Assembled in crate)

Width	Depth	Height	Weight	
73"	82"	86"	3638Lbs	
186cm	207cm	218cm	1650Kg	

#### Shipping Specifications (Unassembled in crates)

	Width	Depth	Height	Weight
Crate 1	82"	43"	85"	4520Lb
Cruie i	208cm	108cm	216cm	(Total)
Crata 2	70"	58"	54"	2050Kg
Crate 2	178cm	148cm	136cm	(Total)

Shipping weight and dimensions are approximate and will change based on tiling selection, sill inclusion and fuel type.

