

NAPOLI-145 ROTATING OVEN

Code: • N-145

Fuel Options: • N-145G-Gas

Baking Surface:

Rotating

Overview

This latest addition to our wood-fired pizza ovens has already seduced pizza makers across Europe and North America. Its bold shape and vibrant style makes the Napoli the perfect focal point in your restaurant and a great conversation piece for your patrons.

Rotating ovens are ideal for fast-paced, high volume baking while still emphasizing production quality. It allows you to minimize the number of staff required, and maximize the use of your workspace.

Pizza Capacity

8"	10"	12"	14"	16″	18″	20"
31	21	15	10	8	7	5

Standard Features

- Constructed with vibrated refractory stone
- Suitable for various foods: pizza, pita, bread, slow cooking meat & fish
- Heats up rapidly up to 950° Fahrenheit (510°C)
- Efficient temperature maintenance with no heat loss
- Heavy duty steel stand
- Rotating refractory stone baking surface
- Touch screen rotation controller, also controls gas on gas equipped ovens.

Certification

• ETL approved for Canada/USA

Warranty Information

- 4 Year deck and dome refractory stone warranty
- 1 Year parts and labour warranty



Images for demonstrative purposes only. Equipment shown may not be included in your custom quote. Images are not to scale. Consult quote for custom options.

Standard Finish

- Plain unfinished
- Additional colours or finishes are extra (see quote)


Customization Options


- Delivered assembled or assembled on site.
- Custom mosaic colour, pattern and branding
- Several door options, sizes and colours available (See brochure)
- Granite mantle
- Left or right burner position (gas/combi ovens)
- Propane or Natural Gas (gas/combi ovens)
- Debris collector
- Oven tools






NAPOLI-145 ROTATING OVEN N-145








Clearance requirement is 3" (8cm) on all sides and 6" (16cm) on the top. Optional granite mantle pictured

Fuel Position

Left side standard, right side optional.



Gas Requirements (if equipped)

- 99,000 BTUs, 3⁄4" NPT
- Inlet pressure for natural gas 7" water column
- Inlet pressure for liquid propane gas 11" water column Gas components must be accessible at all times for maintenance purposes.

Venting Requirements

Vent Type	Gas
Direct Vent	✓
Hood Vent	✓

- The oven is vented through a $73\!\!/_4$ " round duct collar.

- Direct Venting requires a double wall chimney pipe.
- Direct vent flue adapter available: 73/4"-8"
- Hood Venting requires installation under a type 1 exhaust hood. Installation & venting is subject to the local authorities approval.

Oven base height is $81^{\circ}(205cm)$. The legs may be extended by $5\frac{3}{10}(15cm)$ to increase height to $86\frac{3}{10}(220cm)$ & the deck to $47\frac{3}{10}(120cm)$.

Electrical Information

All rotating ovens supplied with a state-of-the-art touch screen controller to control rotation, and gas if equipped.

Controller	Power Plug		Cord	
Touch Screen	220V/1phase	NEMA 6-15P 🕀	9'	274cm

Size Specifications

Oven Specifications					
Baking Area	Width	Depth	Height	Weight	
ø 57¼"	79"	87"	81"	4700Lbs	
ø 145cm	200cm	220cm	205cm	2100Kg	

Shipping Specifications (Assembled in crate)

Width Depth		Height	Weight	
85"	93"	86"	5137Lbs	
217cm	237cm	218cm	2330Kg	

Shipping Specifications (Unassembled in crates)

	Width	Depth	Height	Weight
Crate 1	82"	54"	87"	5512Lb
	208cm	138cm	221cm	(Total)
Crate 2	74"	61"	63"	2500Kg
	188cm	156cm	161cm	(Total)

Shipping weight and dimensions are approximate and will change based on tiling selection, sill inclusion and fuel type.

