COMMERCIAL

Refrigeration Equipment Reach-In Freezer, 1 Door, 25 cu.ft - Stainless Steel (R290)

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738279 (KCHRI25R1DFE)

1-door reach-in freezer, stainless steel, 25 cubic feet, R290 refrigerant gas, -8/+5°F - Energy star

Short Form Specification

Item No.

1 full door freezer with door and bottom panel in 430 stainless steel, exterior back, side and top panels in prepainted steel; interior back, side, top and bottom panels in white High Impact Polystyrene. Control with cabinet temperature display. Self-closing and on-site reversible door feature with lock and key. Temperature range: - 8 °F min / 5 °F max.

R290 gas in the refrigeration circuit. ETL Safety and Sanitation certifications. 3/5 Years warranty.

Main Features

- External temperature display.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- · Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.
- Back bottom mounted cooling unit guarantee an easy access and cleaning.

Construction

- · Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.
- · PVC shelves.

APPF	ROVAL
-------------	-------



Refrigeration Equipment Reach-In Freezer, 1 Door, 25 cu.ft - Stainless Steel (R290)


30.59°(777mm) 30.59°(777mm) 57.64°(1464mm)

57.64*(1464mm)
25.79*(655mm)
2.95*(75mm)

111*(580mm)

111*(580mm)

El = Electrical connection





Supply voltage:

738279 (KCHRI25R1DFE)115 V/1 ph/60 Hz
Current consumption: 2.3 Amps
Plug type: USA NEMA 5-15P

Key Information:

Door hinges: Right Side

Capacity (Cu.Ft.) 25

External dimensions, Width: 30 9/16" (776.99 mm)

External dimensions, Depth: 28 3/4" (730 mm)

External dimensions, Height: 77 9/16" (1970 mm)

Number and type of doors: 1; Full

Number and type of grids

 (included):
 3 - Vinyl-Coated steel

 Type of external material:
 Prepainted Steel

 Type of internal material:
 White Polystyrene

External Door material: 430 AISI
Warranty: 3 / 5 years
External door material: Stainless Steel

Refrigeration Data

Compressor Horsepower: 1/6
Refrigerant type: ;R290
Operating temperature min.: -7.6 °F
Operating temperature max.: 5 °F
Condenser type: Fin & tube
Defrost type: auto defrost









Top